

Saved: 01 DEC 2012 02:42:19



Acquisition: Sampling Mode real time, High Resolution
Analog Memory Depth automatic 1.000 kpts, Digital 401 pts
Analog Sampling Rate automatic 5.00 GSa/s, Digital automatic 2.00 GSa/s
Analog Averaging off, Interpolation Auto

Channel 1: Scale 100 mV/, Offset 0.0 V, Skew 0.0 s
Coupling DC, Impedance 50 Ω

Horizontal: Scale 1.00 ns/, Position 0.0 s, Reference center

Trigger: Mode edge, Source Channel 1, Level -151 mV, Slope falling
AND (Qualifier) Source Channel 3, Level 94 mV, Value L
Sweep triggered, Sensitivity normal, Holdoff Time 100 ns

Measure:

Meas	All Edges	Fall time(1*)	Rise time(1*)
Current		565.6 ps	592.6 ps
Mean		594.3 ps	1.5472 ns
Min		565.6 ps	567.4 ps
Max		616.7 ps	3.5681 ns
Range (Max-Min)		51.1 ps	3.0007 ns
Std Deviation		16.7 ps	1.4749 ns

Number of Meas	6	6
Meas Window	All Data	All Data
Drag&Drop Time		
Edge Direction	Falling	Rising

Markers:

Meas All Edges	Fall time(1*)	X	Y
Current	565.6 ps	A—(1) = -444.7 ps	-32.13 mV
Mean	594.3 ps	B---(1) = 120.8 ps	-287.95 mV
Min	565.6 ps	Δ = 565.6 ps	-255.81 mV
Max	616.7 ps	1/ Δ X = 1.7681 GHz	
Range (Max-Min)	51.1 ps		
Std Deviation	16.7 ps		
Number of Meas	6		
Meas Window	All Data		
Drag&Drop Time			
Edge Direction	Falling		