



VS Vision Systems GmbH

Industrielle Bildverarbeitung

Aspeloh 27A; 22848 Norderstedt

Tel : +49 (40) 528 401-0

Fax : +49 (40) 528 401-99

eMail: Multi@visionsystems.hh.eunet.de

Pinbelegung des DB37 Steckers (auf der VScom 400 PRO, PCI und VScom C104 PRO)

DB37

1	NC	17	DSR 1	33	TX 2
2	DCD 3	18	RTS 1	34	DCD 1
3	GND 3	19	TX 1	35	GND 1
4	CTS 3	20	RI 3	36	CTS 1
5	RX 3	21	DTR 3	37	RX 1
6	RI 4	22	DSR 3		
7	DTR 4	23	RTS 3		
8	DSR 4	24	TX 3		
9	RTS 4	25	DCD 4		
10	TX 4	26	GND 4		
11	DCD 3	27	CTS 4		
12	GND 2	28	RX 4		
13	CTS 2	29	RI 2		
14	RX 2	30	DTR 2		
15	RI 1	31	DSR 2		
16	DTR 1	32	RTS 2		

Pinbelegung des DB25 Steckers (male)

Pin 2	Tx
Pin 3	Rx
Pin 4	RTS
Pin 5	CTS
Pin 6	DSR
Pin 7	GND
Pin 8	DCD
Pin 20	DTR
Pin 22	RI