

Carbon Target Parameters and Particle Distributions for Front End Study (Discussion)

X. Ding

AAG meeting, BNL

Aug 27, 2015

Introduction

- MARS15 (BNL Spot Cluster)
- ROOT based geometry setting without BE windows for 20t02T5m and 20to 4T5m configuration (Carbon target, 1.8 g/cm^3)
- No SMIN card and 400,000 events
- KE at 6.75 GeV, 5 micron beam emittance, launched at $z = -100 \text{ cm}$ (other beam emittance?)
- Collect all particles at $z = 50 \text{ m}$ with KE selection of min. of 40 MeV and max. of 180 MeV or 300 MeV
- Particle distribution at $z = 2 \text{ m}$ and 5 m (other location ?) for Front End Study ($N = 400,000$ or $2000,000?$).


Carbon Target Parameters for Front End Study ?

- Target Length: 100 cm
- Target Radius: 1 cm
- Beam Radius: 0.25 cm
- Beam Angle or Target Angle: 65 mrad
- Beam/Target Crossing Angle: 0 mrad

Backup


20to4T5m Configuration

(TR = 0.8 cm, BR = 0.2 cm, CA = 0, BA = 65 mrad)




20to4T5m Configuration

(LEN = 100 cm, TR/BR = 4, CA = 0, BA = 65 mrad)




20to4T5m Configuration

(LEN = 100 cm, TR = 0.8 cm, BR = 0.2 cm, CA = 0)




20to4T5m Configuration

(LEN = 100 cm, TR = 0.8 cm, BR = 0.2 cm, BA = 65 mrad, CA = 0)




20to2T5m Configuration

(TR = 0.8 cm, BR = 0.2 cm, CA = 0, BA = 65 mrad)




20to2T5m Configuration

(LEN = 100 cm, TR/BR = 4, CA = 0, BA = 65 mrad)



20to2T5m Configuration

(LEN = 100 cm, TR = 0.8 cm, BR = 0.2 cm, CA = 0)



20to2T5m Configuration

(LEN = 100 cm, TR = 0.8 cm, BR = 0.2 cm, BA = 65 mrad, CA = 0)

