

#### nTOF11 Hg System Design Status

Van Graves Tony Gabriel, Phil Spampinato Collaboration Meeting – Princeton University 29-30 Apr 2005


> OAK RIDGE NATIONAL LABORATORY U.S. DEPARTMENT OF ENERGY

### **Access Restrictions**

TT2

TT2A


- Prior to CERN trip, assumed component footprint restriction was 1.3m X 3m
- Measurements indicate additional length available
  - New size restriction 1.3m X 4.4m



SCALE 1:184

**OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY** 






#### OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



### **Baseline Concept Presented at Berkeley Collaboration Meeting**

- Hg piston pump actuated by dual hydraulic cylinders
- Hg capacity for 20sec jet duration (35 liters)
- Hg system length required assembly inside TT2A tunnel




OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



#### **Design Work Since CERN Meetings**

- Pistons resized to eliminate intunnel assembly of target module
- Hg jet duration decreased from 20sec to 12sec
  - Maximum volume required decreased from 35 liters to 23 liters
- Baseplate reconfigured to stay within facility size constraints
- Target/solenoid integration details
  - Hg delivery system size reduction
  - Target cart design optimization
  - Magnet base support


#### OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY






# **Hg Delivery System**

- Reduced length
- Changed sump design
- Refined cart details




OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY





#### **Stray Field Effects**

- Initial discussions with ORNL Fusion Division engineers indicate stray fields will tend to pull iron pistons toward magnetic center
- Effects need to be quantified




OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



#### **Carrier Baseplate**

- Transports Hg system inside tunnel
- Rollers removed once in position
- Rails for Hg system cart wheels
- Will have mechanism to lock cart in place




OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



#### **Common Baseplate**

- Same design as carrier baseplate, just longer
- Rollers used to grossly align solenoid to beam
- Provides lateral movement of solenoid for alignment to beam once rollers removed




OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



### **Baseplate Mobility Issues**

- Method needed to remove rollers from baseplates
  - Lift from end or underneath?
  - CERN/MIT or nTOF11 provide?
- How to interface to CERN "turtle"
- How accurately can baseplate be aligned to beam using rollers?
- Lifting method TBD




OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



# **Target Cart Design**

 Hg system shipped on cart and carrier




OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



# **Cart Details**


- High capacity track rollers can withstand vertical & side loads
- UHMW sheet provides sliding surface for lateral movement of Hg system using jackbolts
- Hg system fixed to top plate, final position locked using nut/bolt



OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY




#### Installation Sequence Part 1 (Out-ofbeam)





OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



#### **Installation Sequence Part 2 (In-beam)**








- Common baseplate can go in beam line prior to Hg system install if beam attenuator is far enough away
- Hg system pulled onto common baseplate using strap winch
- Jacking system needed to remove rollers
- Blocks under leveling feet to provide adequate elevation

OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



#### **Baseplate Still Too Long**

 Adding sliding plate and leveling jacks under solenoid has pushed baseplate closer to floor



OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



# **Alignment Adjustments**

- Nominal nozzle position relative to secondary containment will be measured at ORNL
- CERN beam locating devices should precisely position system relative to beam
- Propose using initial beam shot(s) to refine jet position
  - Optical diagnostics will show beam/jet interaction location
  - Cart lock plates have jackscrews to provide fine adjustment of target insertion depth
  - Lateral adjustment of magnet & Hg system also available





## **Current Design Issues**

- Length optimization
- Baseplate interface with CERN "turtle"
- Lifting methods, lift points
- Stray field effects on pistons & cylinders
- Beam alignment details



# **Remaining Work**

- Lateral restraints
- Winch assembly
- Alignment fiducials
- Replaceable nozzle
- Plenum optimization
- Beam window integration

OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY

